

2017 Version 1.0

DURUN TBR

PRODUCT CATALOG



www.hstyre.com
E-mail: duruntyre@126.com





SHANDONG HABLEAD RUBBER CO.,LTD

INTRODUCTION

Shandong Habilead Rubber Co., LTD belongs to Shandong Huasheng Rubber Group. It is located in the coast of the Bohai Sea, the Yellow River Blue Economic Area center city --Dongying city, superior position, and convenient transportation. It is a large enterprise that combined PCR and TBR research development, manufacture, sale, independent import and export trade. Habilead insist to be better and perfect, focus on the introduction of advanced technology and high-end equipment, develop and produce high-grade precision and sophisticated products, creating a road of product differentiation. The main brands are DURUN, BANNERS, GOLDWAY, and HABLEAD. DURUN brand is awarded "China well-known trademark" by the state trademark bureau.

Habilead will be adhering to the business philosophy of "market-oriented, customer-centric, technology-supported"; With the development path of "talent-enterprises, science and technology enterprises, quality first", Habilead will provide high-quality, high-performance products to all customer as its responsibility and develop by the road of "excellent quality, leading the future".



www.hstyre.com



SHANDONG HABILEAD RUBBER CO., LTD





YTH1 P06

YTH2 P08

YTH3 P09

YTH4 P10

YTH6 P11

YTH7 P12

YTH8 P13

YTH10 P14

YTH12 P15

YTH13 P16

YTH15 P17



YTH18 P18

YTH19 P19

YT102 P20

YT902 P21

YT903 P22

YT906 P23

YT907 P24

YT908 P25

YT919 P26

YT909 P27



SHANDONG HABILEAD RUBBER CO.,LTD

Service Hotline: 0546-7727700

E-Mail: duruntyre@126.com

www.hstyre.com

YTH1

TBR

© Suitable for various road conditions



Size	PR	SS	Rim	LI	TD (mm)
6.50R16	10	L	5.50F	107/102	10.5
6.50R16	12	L	5.50F	110/105	10.5
7.00R16	12	L	5.50F	115/110	11
7.00R16	14	L	5.50F	118/114	11
7.50R16LT	12	K	6.00G	120/116	11.5
7.50R16LT	14	K	6.00G	122/118	11.5
8.25R16LT	14	K	6.50H	126/122	11.5
8.25R16LT	16	K	6.50H	128/124	11.5
8.25R20	14	K	6.5	136/134	12.5
8.25R20	16	K	6.5	139/137	12.5
9.00R20	14	K	7.0	141/139	13.5
9.00R20	16	K	7.0	144/142	13.5
10.00R20	16	K	7.5	146/143	14.5
10.00R20	18	K	7.5	149/146	14.5
11.00R20	16	K	8.0	150/147	16.5
11.00R20	18	K	8.0	152/149	16.5
12.00R20	18	K	8.5	154/151	16.5
12.00R20	20	K	8.5	156/153	16.5
12.00R24	18	K	8.5	158/155	15.0
12.00R24	20	K	8.5	160/157	15.0
11R22.5	14	K	8.25	144/142	16.0
11R22.5	16	K	8.25	146/143	16.0
315/80R22.5	18	L	9.00	154/151	16.5
315/80R22.5	20	L	9.00	156/150	16.5
12R22.5	16	L	9.00	150/147	14.5
12R22.5	18	L	9.00	152/149	14.5



All Position
Recommended



Classic 3 grooves design
Designed for different complicated conditions.



Wear-resisting formula

YTH2

TBR

○ Suitable for high way and regional road conditions



Size	PR	SS	Rim	LI	TD (mm)
9.00R20	14	K	7.0	141/139	15.0
9.00R20	16	K	7.0	144/142	15.0
10.00R20	16	K	7.5	146/143	17.0
10.00R20	18	K	7.5	149/146	17.0
11.00R20	16	K	8.0	150/147	17.0
11.00R20	18	K	8.0	152/149	17.0
10R22.5	14	L	7.50	141/139	15.0
10R22.5	16	L	7.50	144/142	15.0
11R22.5	14	K	8.25	144/142	17.0
11R22.5	16	K	8.25	146/143	17.0



All Position

○ Recommended



4 grooves design provides good drainage performance.
Continuous tire shoulder prevents irregular wear.



Wear-resisting formula





YTH3



◎ Suitable for normal road condition and middle distance



Size	PR	SS	Rim	LI	TD (mm)
9.00R20	14	K	7.0	141/139	15.0
9.00R20	16	K	7.0	144/142	15.0
10.00R20	16	K	7.5	146/143	16.0
10.00R20	18	K	7.5	149/146	16.0
11.00R20	16	K	8.0	150/147	16.5
11.00R20	18	K	8.0	152/149	16.5
12.00R20	18	K	8.5	154/151	16.5
12.00R20	20	K	8.5	156/153	16.5
12R22.5	18	L	9.00	152/149	14.5
10R22.5	16	L	7.50	144/142	15.0



All Position

◎ Recommended



The combination of transverse and longitudinal pattern makes a good balance of traction and handling.

Super wide section provides driving stability and long mileage.

Optimized bead and belt structure make a strong tire body.

YTH4

TBR

- Suitable for high way condition and long distance



Size	PR	SS	Rim	LI	TD (mm)
215/75R17.5	16	J	6.00	135/133	12.5
225/70R19.5	12	M	6.75	125/123	12.5
225/70R19.5	14	M	6.75	128/126	12.5
235/75R17.5	16	J	6.75	143/141	12.5
245/70R19.5	16	J	7.50	135/133	12.5
255/70R22.5	16	J	7.50	140/137	12.5
265/70R19.5	14	J	7.50	137/134	12.5
265/70R19.5	16	J	7.50	143/141	12.5
275/70R22.5	16	J	8.25	144/141	14.5
275/70R22.5	16	J	8.25	148/145	14.5
11R22.5	14	K	8.25	144/142	14.5
11R22.5	16	K	8.25	146/143	14.5
11R24.5	14	K	8.25	146/143	14.5
11R24.5	16	K	8.25	149/146	14.5
295/75R22.5	14	K	9.00	144/141	14.5
295/75R22.5	16	K	9.00	146/143	14.5
285/75R24.5	14	K	8.25	144/141	14.5
285/75R24.5	16	K	8.25	147/144	14.5



All Position

○ Recommended



Multi-directional sipes on tread provide good heat dissipation and ensure the long mileage.
Special protrusions at the bottom of grooves avoid groove crack and clamping stones.
Continuous tire shoulder prevents irregular wear.



YTH6

TBR

○ Suitable for high way and regional road conditions

Size	PR	SS	Rim	LI	TD (mm)
11R22.5	14	K	8.25	144/142	21.5
11R22.5	16	K	8.25	146/143	21.5
11R24.5	14	K	8.25	146/143	21.5
11R24.5	16	K	8.25	149/146	21.5
295/75R22.5	14	K	9.00	144/141	21.5
295/75R22.5	16	K	9.00	146/143	21.5
285/75R24.5	14	K	8.25	144/141	21.5
285/75R24.5	16	K	8.25	147/144	21.5



Drive or Trailer

● Recommended



High mileage assured with super deep tread.

Special protrusions at the bottom of grooves avoid groove crack and clamping stones.

Lateral blocks provide excellent traction power.

YTH7

TBR

○ Suitable for high way condition



Size	PR	SS	Rim	LI	TD (mm)
12R22.5	16	L	9.00	150/147	14.5
12R22.5	18	L	9.00	152/149	14.5
295/80R22.5	16	L	9.00	150/147	14.5
295/80R22.5	18	L	9.00	152/149	14.5
13R22.5	16	K	9.75	152/149	14.5
315/80R22.5	18	L	9.00	154/151	14.5
315/80R22.5	20	L	9.00	156/150	14.5



Steer or Trailer

○ Recommended



Compact pattern design provides longer mileage.
4 straight grooves bring great steering performance
Continuous tire shoulder prevents irregular wear.

YTH8

TBR

○ Suitable for high way and regional road conditions



Size	PR	SS	Rim	LI	TD (mm)
295/80R22.5	16	L	9.00	150/147	21.5
295/80R22.5	18	L	9.00	152/149	21.5
315/80R22.5	18	L	9.00	154/151	22.5
315/80R22.5	20	L	9.00	156/150	22.5
12R22.5	16	L	9.00	150/147	17.0
12R22.5	18	L	9.00	152/149	17.0
11R22.5	14	K	8.25	144/142	22.5
11R22.5	16	K	8.25	146/143	22.5



Drive

○ Recommended



Lateral blocks provide excellent traction power.
High mileage assured with super deep tread.



Wear-resisting formula

YTH10

TBR

○ Suitable for high way condition



Size	PR	SS	Rim	LI	TD (mm)
385/65R22.5	18	K	11.75	158	15.0
385/65R22.5	20	K	11.75	160	15.0



Steer or Trailer

○ Recommended



Multi-directional sipes on tread provide good heat dissipation and ensure the long mileage.

Special protrusions at the bottom of grooves avoid groove crack and clamping stones.

Continuous tire shoulder prevents irregular wear.



Y102



○ Suitable for high way condition

Size	PR	SS	Rim	LI	TD (mm)
7.00R16LT	10	L	5.50F	111/107	11.5
7.00R16LT	12	L	5.50F	115/110	11.5
7.50R20	12	L	6.0	128/126	12.5
7.50R20	14	L	6.0	130/128	12.5



All Position

● Recommended



Continuous tire shoulder prevents irregular wear.
Irrregular sequence pattern pitch design reduces noise efficiently.



Wear-resisting formula



YT902



© Suitable for on-off road conditions

Size	PR	SS	Rim	LI	TD (mm)
11.00R20	16	K	8.0	150/147	18.5
11.00R20	18	K	8.0	152/149	18.5
12.00R20	18	K	8.5	154/151	20.0
12.00R20	20	K	8.5	156/153	20.0



Drive or Trailer

 Recommended



Football pattern design and deep groove bring excellent traction and braking ability.
Ultra strong structure provides excellent high load capacity.



Anti-puncture formula

YT903



○ Suitable for on-off road conditions



Size	PR	SS	Rim	LI	TD (mm)
11.00R20	18	K	8.0	152/149	18.5
12.00R20	18	K	8.5	154/151	19.5
12.00R20	20	K	8.5	156/153	19.5
315/80R22.5	18	K	9	154/151	21
315/80R22.5	20	K	9	157/154	21



Drive or Trailer

 Recommended



Arc-shape groove design provides good drainage performance.
Lateral blocks provide excellent traction power.



Anti-puncture formula

YT906

TBR

● Suitable for on-off road conditions



Size	PR	SS	Rim	LI	TD (mm)
7.50R16LT	12	E	6.00G	120/116	18.5
7.50R16LT	14	D	6.00G	122/118	18.5
8.25R16LT	14	E	6.50H	126/122	18.5
8.25R16LT	16	D	6.50H	128/124	18.5
8.25R20	14	E	6.5	136/134	18.5
8.25R20	16	D	6.5	139/137	18.5
10.00R20	16	E	7.5	146/143	25.2
10.00R20	18	D	7.5	149/146	25.2
11.00R20	16	E	8.0	150/147	25.2
11.00R20	18	D	8.0	152/149	25.2
12.00R20	18	E	8.5	154/151	25.2
12.00R20	20	D	8.5	156/153	25.2



Drive or Trailer

● Recommended



Big strong block design improves the off-road ability.

Unique pattern design brings excellent driving and braking ability.



Anti-puncture formula

YT907

TBR

○ Suitable for on-off road condition and short distance



Size	PR	SS	Rim	LI	TD (mm)
7.50R16LT	12	K	6.00G	120/116	14.5
7.50R16LT	14	K	6.00G	122/118	14.5
8.25R16LT	14	K	6.50H	126/122	14.5
8.25R16LT	16	K	6.50H	128/124	14.5
8.25R20	14	K	6.5	136/134	14.5
8.25R20	16	K	6.5	139/137	14.5
9.00R20	14	K	7.0	141/139	16.5
9.00R20	16	K	7.0	144/142	16.5
10.00R20	16	K	7.5	146/143	17.5
10.00R20	18	K	7.5	149/146	17.5
11.00R20	16	K	8.0	150/147	18.5
11.00R20	18	K	8.0	152/149	18.5
12.00R20	18	K	8.5	154/151	18.5
12.00R20	20	K	8.5	156/153	18.5



Drive or Trailer

⊗ Recommended



Special protrusions at the bottom of grooves avoid groove crack and clamping stones.
Lateral blocks provide excellent traction power.



Anti-puncture formula



YT908



◎ Suitable for mix road condition

Size	PR	SS	Rim	LI	TD (mm)
9.00R20	14	K	7.0	141/139	17.5
9.00R20	16	K	7.0	144/142	17.5
10.00R20	16	K	7.5	146/143	18.5
10.00R20	18	K	7.5	149/146	18.5
11.00R20	16	K	8.0	150/147	19.5
11.00R20	18	K	8.0	152/149	19.5
12.00R20	18	K	8.5	154/151	19.5
12.00R20	20	K	8.5	156/153	19.5



Drive

 Recommended



Ultra strong structure provides excellent high load capacity.
Lateral blocks provide excellent traction and braking power.



Anti-crack formula



YT909

TBR

○ Suitable for high way and regional road conditions

Size	PR	SS	Standard Rim	LI	Tread Depth
11R22.5	16	J	8.25	148/145	22.00
12R22.5	16	F	9.00	150/147	23.20
12R22.5	18	F	9.00	152/149	23.20
12.00R20	18	F	8.50	154/151	24.20
12.00R20	20	F	8.50	156/153	24.20



All Position

● Recommended



Big strong block design improves the off-road ability.

Lateral blocks provide excellent traction power.

Special protrusions at the bottom of grooves avoid groove crack and clamping stones.



Anti-puncture formula

YT919

TBR

○ Suitable for on-off road condition and short distance



Size	PR	SS	Rim	LI	TD (mm)
12.00R20	18	F	8.5	154/151	23.2
12.00R20	20	F	8.5	156/153	23.2
11.00R20	16	F	8.0	150/147	23.2
11.00R20	18	F	8.0	152/149	23.2
9.00R20	14	F	7.0	141/139	19.0
9.00R20	16	F	7.0	144/142	19.0



Drive

○ Recommended



Big strong block design improves the off-road ability.

Lateral blocks provide excellent traction power.

Special protrusions at the bottom of grooves avoid groove crack and clamping stones.



Anti-puncture formula