

SIZE	INTERIOR DIMENSIONS	DOOR OPENING	TOP OPENING	WEIGHT kg/lb			VOLUME
				max gross	tare	max payload	
<p>20' DRY 20' x 8' x 8'6"</p>	<p>L: 5,896 mm 19'4 1/8" W: 2,350 mm 7'8 1/2" H: 2,393 mm 7'10 3/16"</p>	<p>W: 2,339 mm 7'8 1/16" H: 2,274 mm 7'5 1/2"</p>		<p>30,480 67,200</p>	<p>2,280 5,030</p>	<p>28,200 62,170</p>	<p>33.0 cbm 1,165 cu ft</p>
<p>40' HIGH CUBE DRY 40' x 8' x 9'6"</p>	<p>L: 12,032 mm 39'5 11/16" W: 2,350 mm 7'8 1/2" H: 2,697 mm 8'10 1/8"</p>	<p>W: 2,340 mm 7'8 1/8" H: 2,577 mm 8'5 7/16"</p>		<p>32,500 71,650</p>	<p>3,880 8,554</p>	<p>28,620 63,100</p>	<p>76.0 cbm 2,684 cu ft</p>
<p>40' DRY 40' x 8' x 8'6"</p>	<p>L: 12,032 mm 39'5 11/16" W: 2,350 mm 7'8 1/2" H: 2,393 mm 7'10 3/16"</p>	<p>W: 2,340 mm 7'8 1/8" H: 2,274 mm 7'5 1/2"</p>		<p>32,500 71,650</p>	<p>3,700 8,157</p>	<p>28,800 63,493</p>	<p>67 cbm 2,366 cu ft</p>
<p>20' REEFER 20' x 8' x 8'6" Temp +30°C to -30°C</p>	<p>L: 5,451 mm 17'10 9/16" W: 2,290 mm 7'6 1/8" H: 2,167 mm 7'1 5/16" * * Height to red load line</p>	<p>W: 2,290 mm 7'6 1/8" H: 2,212 mm 7'3 1/16"</p>		<p>30,480 67,200</p>	<p>2,990 6,591</p>	<p>27,490 60,600</p>	<p>27 cbm 953 cu ft</p>
<p>40' HIGH CUBE REEFER 40' x 8' x 9'6" Temp +30°C to -30°C</p>	<p>L: 11,580 mm 37'11 7/8" W: 2,275 mm 7'5 6/10" H: 2,415 mm 7'11 1/10" * * Height to red load line</p>	<p>W: 2,276 mm 7'5 9/16" H: 2,471 mm 8'1 1/4"</p>		<p>34,000 74,957</p>	<p>4,520 9,965</p>	<p>29,480 64,992</p>	<p>67.5 cbm 2,384 cu ft</p>
<p>40' HIGH CUBE STARFRESH 40' x 8' x 9'6" Controlled atmosphere</p>	<p>L: 11,578 mm 37'11 13/16" W: 2,280 mm 7'5 3/4" H: 2,425 mm 7'11 1/2" * * Height to red load line</p>	<p>W: 2,278 mm 7'5 11/16" H: 2,473 mm 8'1 5/16"</p>		<p>34,000 74,957</p>	<p>4,600 10,140</p>	<p>29,400 64,992</p>	<p>64 cbm 2,261 cu ft</p>
<p>40' MAGNUM 40' x 8' x 9'6" Temp +30°C to -35°C</p>	<p>L: 11,578 mm 37'11 13/16" W: 2,280 mm 7'5 3/4" H: 2,450 mm 8'1 1/2" * * Height to red load line</p>	<p>W: 2,276 mm 7'5 9/16" H: 2,471 mm 8'1 1/4"</p>		<p>34,000 74,957</p>	<p>4,620 10,185</p>	<p>29,380 64,772</p>	<p>64 cbm 2,261 cu ft</p>
<p>20' OPEN TOP 20' x 8' x 8'6"</p>	<p>L: 5,919 mm 19'5" W: 2,346 mm 7'8 5/16" H: 2,286 mm 7'6"</p>	<p>W: 2,286 mm 7'6" H: 2,253 mm 7'4 11/16"</p>	<p>L: 5,490 mm 18'1 1/16" W: 2,223 mm 7'3 1/2"</p>	<p>30,480 67,196</p>	<p>2,280 5,027</p>	<p>28,000 61,728</p>	
<p>40' OPEN TOP 40' x 8' x 8'6"</p>	<p>L: 12,192 mm 40' W: 2,338 mm 7'8" H: 2,289 mm 7'6 1/16"</p>	<p>W: 2,289 mm 7'6 1/16" H: 2,253 mm 7'4 11/16"</p>	<p>L: 11,810 mm 38'8 25/26" W: 2,223 mm 7'3 1/2"</p>	<p>32,700 72,090</p>	<p>4,000 8,818</p>	<p>28,700 63,728</p>	
<p>40' HIGH OPEN TOP 40' x 8' x 9'6"</p>	<p>L: 12,192 mm 40' W: 2,348 mm 7'8 3/8" H: 2,653 mm 8'8 4/9"</p>	<p>W: 2,388 mm 7'8" H: 2,580 mm 8'5 9/12"</p>	<p>L: 11,810 mm 38'8 25/26" W: 2,223 mm 7'3 1/2"</p>	<p>30,480 67,196</p>	<p>4,000 8,818</p>	<p>26,480 58,377</p>	
<p>40' FIXED CORNER FLAT RACK 40' x 8' x 8'6"</p>	<p>L: 12,192 mm 40' W: 2,438 mm 8' H: 1,940 mm 6'4 3/8"</p>	<p>12,080 mm 39'7 9/16"</p>	<p>11,796 mm 38'8 3/8"</p>	<p>40,000 88,183</p>	<p>5,500 12,125</p>	<p>34,500 76,058</p>	<p>2,114 6'11 3/16"</p>
<p>40' FLUSH FOLD FLAT RACK 40' x 8' x 8'6"</p>	<p>L: 12,192 mm 40' W: 2,438 mm 8' H: 1,940 mm 6'4 3/8"</p>	<p>12,058 mm 39'6 11/16"</p>	<p>11,662 mm 38'3 1/8"</p>	<p>40,000 88,183</p>	<p>5,500 12,125</p>	<p>34,500 76,058</p>	<p>2,224 7'3 1/2"</p>
<p>40' HIGH FLAT RACK 40' x 8' x 9'6"</p>	<p>L: 12,192 mm 40' W: 2,438 mm 8' H: 2,260 mm 7'4 29/30"</p>	<p>12,058 mm 39'6 11/16"</p>	<p>11,662 mm 38'3 1/8"</p>	<p>52,500 111,741</p>	<p>5,300 11,684</p>	<p>47,200 104,056</p>	<p>2,224 7'3 1/2"</p>